

# Birth Weight Part Four: Miscellaneous Examples

## Table of contents

---

bweight4.sas	Correct Likelihood Ratio Test in the Presence of Missing Data
bweight5.sas	Likelihood ratio test with less output
bweight6.sas	Do a Wald test "Manually" with proc iml
bweight7.sas	Probit example

---

```
/* bweight4.sas Try to get a clean LR test */
%include 'bweightread.sas';
title2 'Correct Likelihood Ratio Test in the Presence of Missing Data';

proc logistic;
  title3 'Full model, all the data';
  model low (event=last) = age lwt smoke ptl ht ui ftv r2 r3;

proc logistic;
  title3 'Reduced model, all the data';
  model low (event=last) = age lwt smoke ptl ht ui ftv;

/* G2 = 208.753 - 201.285 = 7.468, df=2 */

proc logistic;
  title3 'Forced stepwise, all the data';
  model low (event=last) = age lwt smoke ptl ht ui ftv r2 r3
    / selection=forward start=7 slentry=1.00 ;

/* Same G2 as above */

data chopped;
  set bigbaby;
  if _n_ < 30 then r2=.;

proc freq; tables r2;

proc logistic;
  title3 'Full model, chopped data';
  model low (event=last) = age lwt smoke ptl ht ui ftv r2 r3;

proc logistic;
  title3 'Reduced model, chopped data (should be same as reduced above)';
  model low (event=last) = age lwt smoke ptl ht ui ftv;

/* G2 = 208.753 - 174.107 = 34.646, df = 2, a disaster */

proc logistic;
  title3 'Forced stepwise, chopped data';
  model low (event=last) = age lwt smoke ptl ht ui ftv r2 r3
    / selection=forward start=7 slentry=1.00 ;

/* G2 = 181.014 - 174.107 = 6.907, df = 2. That's better! */
```

bweight4.lst Just output from the last proc logistic

-----  
Low Birth Weight Data  
Correct Likelihood Ratio Test in the Presence of Missing Data  
Forced stepwise, chopped data

7

The LOGISTIC Procedure

Model Information

Data Set	WORK.CHOPPED	
Response Variable	low	Low Birth Weight
Number of Response Levels	2	
Model	binary logit	
Optimization Technique	Fisher's scoring	

Number of Observations Read	189
Number of Observations Used	160

Response Profile

Ordered Value	low	Total Frequency
1	2500 g +	101
2	Under 2500 g	59

Probability modeled is low='Under 2500 g'.

NOTE: 29 observations were deleted due to missing values for the response or explanatory variables.

Forward Selection Procedure

Step 0. The following effects were entered:

Intercept age lwt smoke ptl ht ui ftv

Model Convergence Status

Convergence criterion (GCONV=1E-8) satisfied.

Model Fit Statistics

Criterion	Intercept Only	Intercept and Covariates
AIC	212.652	197.014
SC	215.727	221.616
-2 Log L	210.652	181.014

Testing Global Null Hypothesis: BETA=0

Test	Chi-Square	DF	Pr > ChiSq
Likelihood Ratio	29.6375	7	0.0001
Score	27.7530	7	0.0002
Wald	22.5177	7	0.0021

Residual Chi-Square Test

Chi-Square	DF	Pr > ChiSq
6.8536	2	0.0325

Step 1. Effect r2 entered:

Model Convergence Status

Skipping ...

Step 2. Effect r3 entered:

Model Convergence Status

Convergence criterion (GCONV=1E-8) satisfied.

Model Fit Statistics

Criterion	Intercept Only	Intercept and Covariates
AIC	212.652	194.107
SC	215.727	224.859
-2 Log L	210.652	174.107

Testing Global Null Hypothesis: BETA=0

Test	Chi-Square	DF	Pr > ChiSq
Likelihood Ratio	36.5448	9	<.0001
Score	33.2599	9	0.0001
Wald	26.6550	9	0.0016

NOTE: All effects have been entered into the model.

Summary of Forward Selection

Step	Effect Entered	DF	Number In	Score Chi-Square	Pr > ChiSq
1	r2	1	8	3.1974	0.0738
2	r3	1	9	3.8088	0.0510

Skipping ...

```

/* bweight5.sas: Explore ODS */
%include 'bweightread.sas';
title2 'Likelihood ratio test with less output';

/* Starting with SAS Version 9, every table produced by SAS has a name,
and the Output Delivery System (ODS) allows one to specify what
is printed. The most convenient way to find out the names in a
unix/linux environment is with ods trace. */

data chopped;
  set bigbaby;
  if _n_ < 30 then r2=.;

ods trace on / listing; /* listing option writes trace on list file,
rather than log file (default) */
proc logistic;
  title3 'Forced stepwise, chopped data';
  model low (event=last) = age lwt smoke ptl ht ui ftv r2 r3
    / selection=forward start=7 slentry=1.00 covb;
run; /* Need run statement with ods trace */
ods trace off;

ods select Logistic.NObs
  Logistic.Step0.GlobalTests
  Logistic.Step2.GlobalTests;

proc logistic;
  title3 'Reduced Output: Still must use a calculator';
  model low (event=last) = age lwt smoke ptl ht ui ftv r2 r3
    / selection=forward start=7 slentry=1.00;

/* Comments:

1. It is safer to use Logistic.Step0.GlobalTests etc. rather than
Logistic.Step0.FitStatistics etc., because the global tests show
the df. This lets you verify that you're doing the right test.

2. The names are very systematic, so by counting the number of steps
required to go from the full to the reduced model, you can use
ods select with confidence. There is no need to do ods trace
every time.

3. It is a great relief to be able to look at only PART of the SAS
output.

4. This example barely scratches the surface of what you can do with
the ods system. For example, you can get SAS to write the list
file in html format suitable for posting as a Web page, or it
can write selected tables to SAS data sets for further processing
within the current SAS job, particularly with proc iml.

```

bweight5.lst

-----  
Low Birth Weight Data  
Likelihood ratio test with less output  
Forced stepwise, chopped data

1

The LOGISTIC Procedure

Output Added:

-----  
Name: ModelInfo  
Label: Model Information  
Template: Stat.Logistic.ModelInfo  
Path: Logistic.ModelInfo  
-----

Model Information

Data Set	WORK.CHOPPED	
Response Variable	low	Low Birth Weight
Number of Response Levels	2	
Model	binary logit	
Optimization Technique	Fisher's scoring	

Output Added:

-----  
Name: NObs  
Label: Observations Summary  
Template: Stat.Logistic.NObs  
Path: Logistic.NObs  
-----

Number of Observations Read	189
Number of Observations Used	160

Skipping ...

Forward Selection Procedure

Step 0. The following effects were entered:

Intercept age lwt smoke ptl ht ui ftv

Skipping ...

Output Added:

-----  
Name: FitStatistics  
Label: Fit Statistics  
Template: Stat.Logistic.FitStatistics  
Path: Logistic.Step0.FitStatistics  
-----

Model Fit Statistics

Criterion	Intercept Only	Intercept and Covariates
AIC	212.652	197.014
SC	215.727	221.616
-2 Log L	210.652	181.014

Output Added:

-----  
Name: GlobalTests  
Label: Global Tests  
Template: Stat.Logistic.GlobalTests  
Path: Logistic.Step0.GlobalTests  
-----

Testing Global Null Hypothesis: BETA=0

Test	Chi-Square	DF	Pr > ChiSq
Likelihood Ratio	29.6375	7	0.0001
Score	27.7530	7	0.0002
Wald	22.5177	7	0.0021

Skipping ...

Step 1. Effect r2 entered:

Skipping ...

Step 2. Effect r3 entered:

Skipping ...

Output Added:

-----  
Name: GlobalTests  
Label: Global Tests  
Template: Stat.Logistic.GlobalTests  
Path: Logistic.Step2.GlobalTests  
-----

Testing Global Null Hypothesis: BETA=0

Test	Chi-Square	DF	Pr > ChiSq
Likelihood Ratio	36.5448	9	<.0001
Score	33.2599	9	0.0001
Wald	26.6550	9	0.0016

NOTE: All effects have been entered into the model.

Skipping ...

---

Low Birth Weight Data  
Likelihood ratio test with less output  
Reduced Output: Still must use a calculator

2

The LOGISTIC Procedure

Number of Observations Read           189  
Number of Observations Used           160

Testing Global Null Hypothesis: BETA=0

Test	Chi-Square	DF	Pr > ChiSq
Likelihood Ratio	29.6375	7	0.0001
Score	27.7530	7	0.0002
Wald	22.5177	7	0.0021

Testing Global Null Hypothesis: BETA=0

Test	Chi-Square	DF	Pr > ChiSq
Likelihood Ratio	36.5448	9	<.0001
Score	33.2599	9	0.0001
Wald	26.6550	9	0.0016

(With R)

```
> 36.5448 - 29.6375  
[1] 6.9073
```

```

/* bweight6.sas */
%include 'bweightread.sas';
title2 'Do a Wald test "Manually" with proc iml';

ods trace on / listing; /* listing option writes trace on list file,
                        rather than log file (default) */

proc logistic;
  title3 'The easy way';
  class race / param = ref;
  model low (event='Under 2500 g') = lwt race / covb;
  race: test raceBlack = raceOther = 0;
run;
ods trace off;

ods listing close; /* No output is sent to the list file */
proc logistic;
  title3 'Make SAS data sets with beta-hat and V-hat';
  ods output ParameterEstimates=MLEdata covb=Vdata;
  class race / param = ref;
  model low (event='Under 2500 g')= lwt race / covb;
run;

ods listing; /* Turn output to list file back on now. */

/* Take a look at the SAS data sets that have been written
   by proc logistic */
proc print data=MLEdata;
title3 'Parameter Estimates';
proc print data=Vdata;
title3 'Asymptotic Covariance matrix';

proc iml;
  title3 'Proc IML output';
  use MLEdata;
  read all var {estimate} into betahat;
  print betahat;
  use Vdata;
  read all var {Intercept lwt raceBlack raceOther} into vhat;
  print vhat;
  /* Testing H0: C beta = 0 */
  C = {0 0 1 0,
       0 0 0 1};
  W = (C*betahat)` * inv(C*vhat*C`) * (C*betahat);
  pval = 1-probchi(W,2);
  print "Wald Test for race" W pval;
  print " ";

```



% cat bweight6.lst

-----  
Low Birth Weight Data 1  
Do a Wald test "Manually" with proc iml  
The easy way

The LOGISTIC Procedure

Output Added:

Skipping ...

Linear Hypotheses Testing Results

Label	Wald Chi-Square	DF	Pr > ChiSq
race	5.4024	2	0.0671

-----  
Low Birth Weight Data 2  
Do a Wald test "Manually" with proc iml  
Parameter Estimates

Obs	Variable	Class Val0	DF	Estimate	StdErr	WaldChiSq	Prob ChiSq
1	Intercept		1	0.8057	0.8452	0.9088	0.3404
2	lwt		1	-0.0152	0.00644	5.5886	0.0181
3	race	Black	1	1.0811	0.4881	4.9065	0.0268
4	race	Other	1	0.4806	0.3567	1.8156	0.1778

-----  
Low Birth Weight Data 3  
Do a Wald test "Manually" with proc iml  
Asymptotic Covariance matrix

Obs	Parameter	Intercept	lwt	race Black	race Other
1	Intercept	0.7143	-0.00521	0.022602	-0.1035
2	lwt	-0.00521	0.000041	-0.00065	0.000356
3	raceBlack	0.022602	-0.00065	0.238194	0.0532
4	raceOther	-0.1035	0.000356	0.0532	0.127216

---

Low Birth Weight Data  
Do a Wald test "Manually" with proc iml  
Proc IML output

4

betahat

0.8057102  
-0.015223  
1.0810614  
0.4806029

vhat

0.7142996 -0.005214 0.0226022 -0.103497  
-0.005214 0.0000415 -0.000647 0.0003559  
0.0226022 -0.000647 0.238194 0.0532  
-0.103497 0.0003559 0.0532 0.1272158

W pval

Wald Test for race 5.4023699 0.0671259

Compare earlier output

Linear Hypotheses Testing Results

Label	Wald Chi-Square	DF	Pr > ChiSq
race	5.4024	2	0.0671

```

/* bweight7.sas */
%include 'bweightread.sas';
title2 'Probit example';

/* Just look at parameter estimates and Z-tests */

ods select ParameterEstimates(persist); /* Persist means keep doing it. */
proc logistic;
  title3 'Logistic Regression, for comparison';
  class race / param = ref;
  model low (event='Under 2500 g') = lwt race;
  race: test raceBlack = raceOther = 0;

proc logistic;
  title3 'Probit Regression: p = Phi(x-prime beta)';
  class race / param = ref;
  model low (event='Under 2500 g') = lwt race / link=probit;
  race: test raceBlack = raceOther = 0;

```

---

1

Low Birth Weight Data  
 Probit example  
 Logistic Regression, for comparison  
 The LOGISTIC Procedure  
 Analysis of Maximum Likelihood Estimates

Parameter	DF	Estimate	Standard Error	Wald Chi-Square	Pr > ChiSq
Intercept	1	0.8057	0.8452	0.9088	0.3404
lwt	1	-0.0152	0.00644	5.5886	0.0181
race Black	1	1.0811	0.4881	4.9065	0.0268
race Other	1	0.4806	0.3567	1.8156	0.1778

---

2

Low Birth Weight Data  
 Probit example  
 Probit Regression: p = Phi(x-prime beta)  
 The LOGISTIC Procedure  
 Analysis of Maximum Likelihood Estimates

Parameter	DF	Estimate	Standard Error	Wald Chi-Square	Pr > ChiSq
Intercept	1	0.4620	0.4938	0.8754	0.3495
lwt	1	-0.00904	0.00370	5.9622	0.0146
race Black	1	0.6564	0.2959	4.9216	0.0265
race Other	1	0.2872	0.2151	1.7826	0.1818